



PR-RT-MD40DCA-36

4 MP IP METAL DOME CAMERA

KEY FEATURES

- 1/3" OMNIVISION CMOS SENSOR
- DWDR; WITH IR-CUT
- WATER RESISTANCE: IP65
- MAIN STREAM: 4MP@20-25FPS
- 4MP HD LENS WITH IR-CUT
- SMART IR LED: 15 PCS
- IR RANGE: 20-25M
- INTERNAL POE
- SUPPORT LOW ILLUMINATION

4 MP

DWDR

3.6MM

POE

AGC


IP65



1800-123-3699




www.prizor.in



TECHNICAL SPECIFICATION

Model	PR-RT-MD40DCA-36
IMAGE SENSOR	1/3" OMNIVISION CMOS SENSOR
MAIN PROCESSOR	REALTEK
RESOLUTION	4 MP
EFFECTIVE PIXELS	2560(H)* 1440(V)
TV SYSTEM	PAL/NTSC
ELECTRONIC SHUTTER TIME	AUTO: PAL 1/1-1/10000SEC; NTSC 1/1-1/10000SEC
SYNC SYSTEM	EXTERNAL
USABLE ILLUMINATION	0.1LUX@(F2.1 AGC ON), 0 LUX WITH IR & WARM LED ON
S/N RATIO	≥39DB
SCANNING SYSTEM	PROGRESSIVE
VIDEO OUTPUT	NETWORK
LENS	
FOCUS LENGTH	3.6 MM
FOCUS CONTROL	FIXED
TYPE	HD IR CORRECTED LENS
PIXEL	4 MP
SMART IR LED	15 PCS(COLOR-0.1LUXAGC ON)
INFRARED DISTANCE	20 TO 25 M
IR POWER ON	CDS AUTO CONTROL
IR STATUS	UNDER 10 LUX BY CDS
ONVIF	SUPPORTS ONVIF 20.6



TECHNICAL SPECIFICATION

NETWORK	PR-RT-MD40DCA-36
ETHERNET	RJ-45 (10/100BASE-T)
PROTOCOL	IPV4, HTTP, TCP/IP, NTP, RTSP, UDP, SMTP, DNS
POE	SUPPORTS IEEE 802.3AF
AUDIO CODEC	G711U/G711A
MAIN STREAM	4MP@25FPS
SUB STREAM	640*360VGA@25FPS, 352*288@25FPS
IE BROWER	IE8-11, GOOGLE CHROME, FIREFOX
DAY/NIGHT	IMAGE IN NIGHT / B&W (IR-CUT)
COMPRESSION	H.265/H.264/SUPPORTS RECORD AVI FORMAT
IMAGE CONFIGURATION	SATURATION/BRIGHTNESS/CONTRAST/SHARPNESS, MIRROR, 3D NR, WHITE BALANCE, BLC, FLK(FLICKER CONTROL)
MOTION DETECTION	SUPPORTS
PRIVACY MASKING	4 RECTANGULAR ZONE
WDR	YES
RECORDING MODE	NVR
LANGUAGE	ENGLISH
HOUSING	METAL BODY, IP65
OPERATION TEMPERATURE	-20°C~+60°C RH95% MAX
STORAGE TEMPERATURE	-20°C~+60°C RH95% MAX
POWER SOURCE	DC12V±10%, 2000MA
WEIGHT	400 G

