



PV-D2420PBA

2.4MP HD COLOR VIEW AUDIO
PLASTIC BULLET CAMERA

KEY FEATURES

- 1/2.9" SONY CMOS SENSOR
- WDR; WITH IR-CUT
- FULL COLOR VIEW IN NIGHT VISION
- WATER RESISTANCE: IP66
- 2.4MP HD LENS 3.6MM WITH IR-CUT
- 3600K SOFT WARM LIGHT: 4PCS
- IR RANGE: UP TO 20M
- SUPPORT LOW ILLUMINATION, WARM LIGHT DAY/NIGHT FULL COLOR
- INBUILT COXIAL AUDIO SUPPORTED

2.4 MP

3DNR

3.6 MM

24/7
COLOR

AGC

IP66



1800-123-3699



www.prizor.in



TECHNICAL SPECIFICATION

MODEL	PV-D2420PBA
IMAGE SENSOR	1/2.9 SONY CMOS SENSOR
MAIN PROCESSOR	SONY
RESOLUTION	2.4MP
EFFECTIVE PIXELS	1920(H) x 1080(V)
TV SYSTEM	PAL/NTSC
VIDEO INPUT	AHD/TVI/CVI & CVBS
SYNC SYSTEM	EXTERNAL
USABLE ILLUMINATION	0.1LUX@ (F2.1 AGC ON); 0LUX WITH IR
S/N RATIO	≥52DB
SCANNING SYSTEM	PROGRESSIVE
VIDEO OUTPUT	NETWORK
LENS	
FOCUS LENGTH	3.6MM
FOCUS CONTROL	FIXED
TYPE	HD IR CORRECTED LENS
PIXEL	3MP
WARM LED	4PCS(COLOR-0.1LUXAGC ON & 0LUX IR ON)
INFRARED DISTANCE	UP TO 20M
IR POWER ON	CDS AUTO CONTROL
IR STATUS	UNDER 10 LUX BY CDS
IR LED	4PCS 3600K SOFT WARM LIGHT
ICR	SUPPORT ICR EXT/COLOR/BW






PV-D2420PBA

**2.4MP HD COLOR VIEW AUDIO
PLASTIC BULLET CAMERA**

MODEL	PV-D2420PBA
LANGUAGE	ENGLISH, BULGARIAN, POLISH, FARSI, GERMAN, RUSSIAN, FRENCH, KOREAN, PORTUGUESE, JAPANESE, TURKISH, SPANISH, HEBREW, ITALIAN
HOUSING & DIMENSION	PLASTIC BODY 73MM * 73MM * 170, IP66
OPERATION TEMPERATURE	-20° ~ +60° RH95% MAX
STORAGE TEMPERATURE	-20° ~ +60° RH95% MAX
POWER SOURCE	DC12V±10%, 1000MA
WEIGHT	250G



1800-123-3699



www.prizor.in