



PV-D2428PDA

2.4MP HD COLOR VIEW AUDIO PLASTIC DOME CAMERA

KEY FEATURES

- 1/2.9" SONY CMOS SENSOR
- WDR; WITH IR-CUT
- FULL COLOR VIEW IN NIGHT VISION
- WATER RESISTANCE: IP65
- 2.4MP HD LENS 2.8MM WITH IR-CUT
- 3600K SOFT WARM LIGHT: 4PCS
- IR RANGE: UP TO 15M-20M
- SUPPORT LOW ILLUMINATION, WARM LIGHT DAY/NIGHT FULL COLOR
- INBUILT COXIAL AUDIO SUPPORTED

2.4 MP

3DNR

2.8 MM

24/7
COLOR

AGC

IP65



1800-123-3699



www.prizor.in



TECHNICAL SPECIFICATION

MODEL	PV-D2428PDA
IMAGE SENSOR	1/2.9 SONY CMOS SENSOR
MAIN PROCESSOR	SONY
RESOLUTION	2.4MP
EFFECTIVE PIXELS	1920(H) x 1080(V)
TV SYSTEM	PAL/NTSC
VIDEO INPUT	AHD/TVI/CVI & CVBS
SYNC SYSTEM	EXTERNAL
USABLE ILLUMINATION	0.1LUX@ (F2.1 AGC ON); 0LUX WITH IR
S/N RATIO	≥52DB
SCANNING SYSTEM	PROGRESSIVE
VIDEO OUTPUT	NETWORK
LENS	
FOCUS LENGTH	2.8MM
FOCUS CONTROL	FIXED
TYPE	HD IR CORRECTED LENS
PIXEL	3MP
WARM LED	4PCS(COLOR-0.1LUXAGC ON & 0LUX IR ON)
INFRARED DISTANCE	UP TO 15M-20M
IR POWER ON	CDS AUTO CONTROL
IR STATUS	UNDER 10 LUX BY CDS
IR LED	4PCS 3600K SOFT WARM LIGHT
ICR	SUPPORT ICR EXT/COLOR/BW






PV-D2428PDA

**2.4MP HD COLOR VIEW AUDIO
PLASTIC DOME CAMERA**

MODEL	PV-D2428PDA
LANGUAGE	ENGLISH, BULGARIAN, POLISH, FARSI, GERMAN, RUSSIAN, FRENCH, KOREAN, PORTUGUESE, JAPANESE, TURKISH, SPANISH, HEBREW, ITALIAN
HOUSING & DIMENSION	PLASTIC BODY 73MM * 73MM * 107, IP65
OPERATION TEMPERATURE	-20° ~ +60° RH95% MAX
STORAGE TEMPERATURE	-20° ~ +60° RH95% MAX
POWER SOURCE	DC12V±10%, 1000MA
WEIGHT	250G



1800-123-3699



www.prizor.in